

ErP Product Fiche In accordance with EU1253/2014 & EU1254/2014



	LO 1233/2014 & LO 1234/201				
(a)	Supplier Name	Vectaire Ltd			
(b)	Model	MIDI			
		Cold	Average		
(c)	Specific Energy Consumption (KWh/(m ² .a))	-81.58	-42.86	-18.06	
	SEC Class	A+	A+	E	
(d)	RVU or NRVU / Unidirectional or Bidirectional	RVU / Bidirectional			
(e)	Type of drive installed	Variable Speed			
(f)	Type of heat recovery system	Recuperative			
(g)	Thermal efficiency of heat recovery	86%			
(h)	Maximum flow rate (m ³ /h)	313			
(i)	Electric power input at maximum flow rate (W)	111.4			
(j)	Sound power level (L _{WA})	46			
(k)	Reference flow rate (m ³ /s)	219			
(l)	Reference pressure difference (Pa)	50			
(m)	Specific Power Input (W/(m³/h))	0.21			
(n)	Control factor	0.65			
	Control typology	Local	Local Demand Control		
(o)	Maximum internal leakage rate	< 5%			
(0)	Maximum external leakage rate		< 5%		
(p)	Mixing rate of non-ducted bidirectional ventilation units not	N1/A			
	intended to be equipped with one duct connection on either supply or extract air side	N/A			
	Position and description of visual filter warning for RVUs				
(q)	intended for use with filters, including text pointing out the				
	importance of regular filter changes for performance and energy	Refer to O&M manual			
	efficiency of the unit				
	For unidirectional ventilation systems, instructions to install	N/A			
(r)	regulated supply/exhaust grilles in the façade for natural air				
	supply/extraction				
(s)	Internet address for disassembly instructions	www.vectaire.co.uk			
(t)	For non-ducted units only: the airflow sensitivity to pressure variations at + 20Pa and – 20 Pa	N/A			
(u)	For non-ducted units only: the indoor/outdoor air tightness in	N/A			
(-)	m ³ /h		T		
(v)	Annual Electricity Consumption per 100m ² (kWh/a)	Cold 693.73	Average 156.73	Warm 111.73	
(w)	Annual Heating Saved (kWh/a)	Cold	Average	Warm	
		9019.49	4610.57	2084.84	
		1 30 13.43	4010.57	2004.04	

